



Nederlands

Installatiehandleiding

Transformator

Geïnstalleerd in 9 stappen

- 1 *Schakel altijd eerst de stroomtoevoer van het lichtnet uit voordat u met elektrische werkzaamheden begint.*
- 2 *Installeer op een goed geventileerde plaats, uit de buurt van warmtebronnen.*
- 3 *Verwijder de afschermkappen zodat de aansluitklemmen van de transformator zichtbaar worden.*
- 4 *Monteer de 230V en de laagspanningsbedrading op de juiste aansluitpunten van de transformator. 230V bedrading op INPUT/Primaire ingang, laagspanningsbedrading op OUTPUT/Secundaire uitgang.*
- 5 *Sluit de uitgangskabels van de ene transformator niet aan op die van een andere.*
- 6 *Gebruik identieke kabellengtes aan de uitgangszijde van de transformator(en) om gelijkmatige lichtniveaus tussen lampen te bereiken.*
- 7 *Zodra de bedrading goed zit bevestigd aan de transformator, monteert u de afschermkappen weer terug op de transformator zodat de bedrading en aansluitklemmen weer volledig afgedekt zijn.*
- 8 *230V Dimmers en schakelaars dienen zich altijd aan de primaire ingang zijde van de transformator te bevinden.*
- 9 *Als u een langere kabel nodig heeft, gebruik dan een gecertificeerde kroonsteen/las klem om een geschikte extra kabel aan te sluiten, zodat er geen blootliggende draden uit de klemmen steken.*



English

Installation manual

Transformer

Installed in 9 steps

- 1 *Always switch off the power supply from the mains before starting any electrical work.*
- 2 *Install in a well-ventilated place, away from heat sources.*
- 3 *Remove the shielding caps to expose the transformer terminals.*
- 4 *Install the 230V and the low voltage wiring on the correct terminals of the transformer. 230V wiring on INPUT/Primary input, low voltage wiring on OUTPUT/Secondary output.*
- 5 *Do not connect the output leads from one transformer to another.*
- 6 *Use identical cable lengths on the output side of the transformer(s) to achieve even light levels between lamps.*
- 7 *Once the wiring is properly attached to the transformer, refit the shielding caps onto the transformer so that the wiring and terminals are completely covered again.*
- 8 *230V Dimmers and switches should always be located on the primary input side of the transformer.*
- 9 *If you require a longer cable, use a certified terminal block/splice terminal to connect a suitable additional cable so that no bare wires protrude from the terminals.*



Nederlands
Installatiehandleiding
Transformator



English
Installation manual
Transformer

